



ELASTOFLEX GUM – *quartz waterpaints*

Quartz water-based paint for exterior based on pure acrylic resin and micronized quartz with high yield and coverage. The presence of elastomeric resins gives the product qualities of good elasticity preventing the cracking phenomena of the paint due to aging. Particularly recommended to give the surface a particular protection and durability.

SPECIFICATIONS

Composition: styrene-acrylic, titanium dioxide, ventilated quartz and selected aggregates

Dried product appearance: matt.

Solid content: 66%±2.

Ash: 51% ± 2

Particle size: 60-70 µ

Viscosity at 20°C: 20.000 cps ± 1.500 cps (a6 20').

Abrasion resistance: excellent.

Average film thickness: 75-80 µ.

Weathering resistance: excellent

Strength of adhesion to the substrate: excellent.

Ph: 8-8,5.

Application: brush, roller.

Dilution: 25% with water.

Yield: 5-6 sqm/L, with two layers according to the substrate.

Drying time: in depth after 18 hours depending on the environmental conditions.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *New surfaces:* be sure that the plaster is completely seasoned (at least 4-5 weeks). Apply a coat of **Primer Consolidante** (Caf). Allow to dry, then complete applying **Elastoflex Gum** (Caf) with brush or roller, spreading the product uniformly; once dry (18-24 hours) apply the second layer.

- *Already painted surface:* if the surface is in good condition, clean it thoroughly with high pressure machine washing and proceed with the application of painting. If the surface is in poor condition, remove the old paint with paint remover **Express** and remove any scraps; eliminate the cracks with stucco, if necessary; then proceed applying a layer of nitro-based primer **Fix Nitro alla Pliolite** (Caf). Then proceed applying **Elastoflex Gum** (Caf) with brush or roller, spreading the product uniformly; once dry (18-24 hours) apply the second layer.

USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

CLIMATIC CONDITIONS


To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between 5 °C and 35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

Protect from frost.

Packaging: 14 L.

Color: white, Allegro color chart, tint on request.

The coloring is possible with the Tinting System 

Washing tools: use water immediately after use.

Specification Item

> Protect all surfaces not subject to application of paint.

> Preparation of the surface by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt. If the surfaces to be treated were covered with organic paints is advisable total removal of these paintings.

> Application by roller or brush of a first coat of water-based quartz paint for outdoor use **Elastoflex Gum** (CAF) followed after 18-24 hours from the application of a second coat of the same product, subject to a consumption refers to two coats of 0, 200 L/sq.m, according to the type of support, after preparing the substrate with a consolidating primer **Primer Consolidante** (CAF).

> All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.