



STUCCO GOTICO – *lime products*

Paste made of lime and natural dyes that allows the realization of smooth and shiny surfaces of great aesthetic effect. Internal and external use.

SPECIFICATIONS

Performance: surface hardness, gloss, high breathability and anchorage to support especially in the case in which the support is made from plaster based on lime. Thanks to its natural composition it prevents the formation of mold. In terms of aesthetics it remembers the finishing of marble and gives prestige to both modern and ancient environments.

Composition: mineral product, based on long seasoned aircraft binders, inorganic mineral pigments and selected fillers of different nature. Organic components less than 5%.

Appearance: glossy, chiaroscuro marble effect.

Weathering resistance: good, even in critical conditions.

Water vapor diffusion: excellent.

Solid content: $66 \pm 2\%$.

Application: stainless steel trowel.

Dilution: ready to use.

Yield: 0,800-1,00 Kg/sqm, depending on the absorbency of the support.

Drying time: 24 hours in normal conditions of temperature and humidity.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *Indoor surface in bad conditions:* after restoring the plaster in the best conditions and he awaited the time required to seasoning, proceed with the application of at least two layers of **Stucco Gotico** (Caf) making the surface as smooth and homogeneous as possible. Allow to dry these first two layers of the product, sanding if necessary. Apply the last coat of the product with movements defined according to the desired final effect: with narrow movements, large, random, regular, linear, etc.. During the step of drying the friction with the stainless steel polishes the surface without the need for additional products. Repeated passages will increase the level of gloss.

- *Indoor surface in good conditions:* on a smooth surface apply at least two layers of product and then proceed with the polishing phase.

- *Outdoor surface:* outdoor applications must be performed on a substrate prepared with MarmosR to have the best performance and durability of adhesion.

Having regard to the significant differences of application and of physical-chemical nature of the surfaces, no responsibility can be attributed to the producer in case of difficulty of adherence of the product or to different chemical reactions that can occur, even on color and, worse, if there is the presence of moisture, salt and extreme temperatures (hot or cold). It is therefore necessary that the applicator uses all due caution that experience suggests. Remember that the plaster truly breathable compounds with hydraulic lime and without cement are the ideal support for cycles of restoration with diffusive paints.

The technical informations contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



CLIMATE CONDITIONS

NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

To avoid compromising the optimal appearance and performance of the product we recommended that it be applied only in specific climate conditions:

- Apply to temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in case of humidity;
- Surface must be protected from rain and damp for approximately 48 hours.

USEFUL TIPS

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

Packaging: 8-24 Kg.

Color: Stucco Gotico color chart.

Washing tools: use water immediately after use.