



ALTAIR – KOSMO decorative line

Decorative paint for interior with metallic effect, silky to the touch. **ALTAIR** is non-flammable and becomes washable after about 3 weeks of application. Altair gives a very elegant and precious metal finish on the walls: the combination of gold and silver bases with the 15 toners, offers a wide range of colors and inimitable results that are perfectly suited to the most sophisticated needs and locations. The extremely smooth consistency of ALTAIR makes possible different methods of application and the realization of decorative effects such as the striped effect, the mosaic effect, the sea effect and the brushed effect, which often require the experience of the applicator.

SPECIFICATIONS

Composition: special acrylic emulsions, unalterable metallic pigments, special additives.

Application: plastic spatula, plastic trowel, decorative paintbrush.

Dilution: ready to use.

Yield: 12 sqm/lt, for 1 coat.

Drying time: to touch 2 hour, hardened in depth 24 hours under normal conditions of temperature and humidity.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- Preparation of the shade: For each color are shown 4 shades, each of which corresponds to a letter A, B, C, D. To obtain the desired shade has to be added to a pack of 2,5 liters of **Altair** Gold or Silver the amount of **Kosmo Concentrato** (Caf) as indicated in the table below:

A	B	C	D
3x70 ml	70 ml.	22 ml. (*)	8 ml. (*)

(*) dosage obtainable with the measuring syringe.

Different doses of Kosmo Concentrato create a range of unlimited color tones

- Surface preparation: Sand down, dust and fill any surface imperfections using putty paste **Dermastuck** (Caf). Apply a coat of water-based acrylic fixative **Hydrocrlil** (Caf), diluted with water to 300%. Allow to dry for at least 4-5 hours and apply two coats of white washable top quality paint **Murinex 030** (Caf) diluted 30-35% by water. Wait at least 5-6 hours between the first and the second coat.

- Application:

- **Brushed effect:** Apply ALTAIR on the wall with the use of a paintbrush, making irregular and crossed movements and allow to dry for at least 12 hours. Repeat the operation in the same way with a second coat.
- **Sea effect:** Apply ALTAIR on the wall with the use of a paintbrush in small areas of about 1mq; use the special foam pad to make circular movements. Allow to dry for at least 12 hours and repeat the operation in the same way with a second coat.

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

- **Striated effect:** Apply ALTAIR in a linear way on the wall with the use of a paintbrush; to create the striated effect, brush gently the wall with the decorative brush, horizontally or vertically. After about 12 hours repeat the operation in the same way with a second coat.
- **Mosaic effect:** Apply ALTAIR on the wall with the use of a paintbrush in small areas of about 1mq; put the squared foam pad on the wall and pull the product as if to draw a horizontal line. Use the same tool to recreate the checkerboard effect, alternating small horizontal and vertical movements along the above-mentioned line. Repeat until covering the whole wall. Repeat the operation in the same way with a second coat.

USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

Protect from frost.

Packaging: 2,5 L.

Color: Altair color chart.

Washing tools: use water immediately after use.

Specification Item

- > Protect all surfaces not subject to application of paint.
- > Preparation of the substrate by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt.
- > Application of one coat of water-based primer **Hydrocril** (Caf) and two coats of washable top quality paint **Murinex 030** (Caf) waiting for the complete drying between each phase.
- > Application of one coat of decorative paint with metallic effect **Altair** (Caf) in the desired effect.
- > All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.