



**NUOVA CAF S.r.l.**

Via L. Einaudi, 6/7\_Z.I. – 61032 Fano (PU)\_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

[www.nuovacaf.it](http://www.nuovacaf.it) - [info@nuovacaf.it](mailto:info@nuovacaf.it)

## **BUCCIATO – acrylic outdoor wall coating**

Bucciato is a textured-finish acrylic wall coating for exterior use. It is formulated with top quality resins and selected quartz aggregates that give maximum breathability and water repellency; it is also resistant to the temperature range, the saltiness, the alkalinity of the sea and the weather conditions. It has an excellent anchorage to the substrate and it provides high protective action of the surfaces for a very long time.

### **SPECIFICATIONS**

**Composition:** vinylversatic copolymers in aqueous dispersion, selected quartz sands, calcium carbonates.

**Appearance of the dried product:** matt.

**Solid content:** 77 ± 2%.

**Particle size:** 500-600 µ.

**Viscosity:** thick paste.

**Abrasion resistance:** excellent.

**Average thickness of coating:** 1-1.5 mm.

**Weathering resistance:** excellent.

**Strength of adhesion to the substrate:** excellent.

**Water repellence:** good.

**Water vapor diffusion:** good.

**Ph:** 8-8,5.

**Application:** specific roller.

**Dilution:** ready to use.

**Yield:** 2 sq.m./L, according to the substrate.

**Drying time:** dried in depth after 18 hours depending on the environmental conditions.

### **METHOD OF USE**

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- **New surfaces:** be sure that the plaster is completely seasoned (at least 4-5 weeks). Apply a coat of **Fix Nitro alla Pliolite** (Caf). Allow to dry, then complete applying a layer of **Microfin Quarz Super** (Caf) by brush or roller: it has recommended a color tone similar to the finish; once dry (18-24 hours) apply **Bucciato** (Caf) by the specific roller, according to the desired effect. Then uniform the thickness created by passing with the roller horizontally and finally vertically upwards.

- **Already painted surface:** eliminate the cracks with stucco, if necessary; then proceed as above.

### **USEFUL TIPS:**

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



CLIMATIC CONDITIONS

**NUOVA CAF S.r.l.**

Via L. Einaudi, 6/7\_Z.I. – 61032 Fano (PU)\_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

[www.nuovacaf.it](http://www.nuovacaf.it) - [info@nuovacaf.it](mailto:info@nuovacaf.it)

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

**Protect from frost.**

**Packaging:** 14 L.

**Color:** white, Allegro color chart, tints on request.

**Washing tools:** use water immediately after use.

## Specification Item

> Protect all surfaces not subject to application of paint.

> Preparation of the surface by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt. If the surfaces to be treated were covered with organic paints is advisable the total removal of these paintings.

> Application by specific roller of the acrylic wall coating **Bucciato** (CAF) with an average thickness of 1-1,5 mm equivalent to a consumption of 0,500 L/sq.m, after preparing the undercoat with a layer of nitro fixative **Fix Nitro alla Pliolite** (CAF) and a coat of quartz paint **Microfin Quarz Super** (CAF) in a similar tone of the finishing.

> All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.