



**NUOVA CAF S.r.l.**

Via L. Einaudi, 6/7\_Z.I. – 61032 Fano (PU)\_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

[www.nuovacaf.it](http://www.nuovacaf.it) - [info@nuovacaf.it](mailto:info@nuovacaf.it)

## DERMASTUCK – *putties*

Wood and wall filler in paste, for interior use for levelling imperfections. It has a high degree of adhesion and it is odorless. It is easy to sand and recoated with any type of paint. It does not form cracks and has considerable resistance.

### SPECIFICATIONS

**Composition:** synthetic polymers, natural thickeners, titanium dioxide, calcium carbonate crystal and amorphous.

**Dried product appearance:** matt.

**Filling power:** excellent.

**Solid content:** 74%  $\pm$  2.

**Ash:** 71% $\pm$ 2.

**Application:** spatula, trowel.

**Dilution:** ready to use.

**Drying time at 20°C:** hardened in depth in 16-24 hours.

### METHOD OF USE

*All substrates must be perfectly dry, free of any crumbly or not well anchored parts, any mold and dirt in general.*

Apply one or more layers of **Dermastuck** (Caf) with spatula or trowel until obtaining a smooth surface. After each layer is recommended to sand the surface to remove any imperfections. Prior to paint apply a coat of water-based fixative **Hydrocril** (Caf).

### CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5°C and +35°C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

### USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

**Packaging:** 0,500 – 1 – 5 – 20 Kg.

**Color:** white.

**Washing tools:** use water immediately after use.

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



**NUOVA CAF S.r.l.**

Via L. Einaudi, 6/7\_Z.I. – 61032 Fano (PU)\_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

[www.nuovacaf.it](http://www.nuovacaf.it) - [info@nuovacaf.it](mailto:info@nuovacaf.it)

## Specification Item

- > Protect all surfaces not subject to application of paint.
- > Application, on the surface already prepared, of putty paste **Dermastuck** (Caf) for levelling wall surfaces or wood.
- > All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.