



DRY SIL – *finishing and protection*

Solvent-based impregnating siliconic, organosiliconic, transparent. It is ideal for the treatment of different alkaline materials and not, such as concrete, stone, brick, fiber cement, terracotta, plaster, etc. ... as it protects the masonry from water infiltration. It has a high depth of penetration and a good adhesiveness towards the wall surfaces, as well as a low moisture absorption even after long exposure to weather and frost. The treatment gives a pearly effect, is permeable to water vapor and blocks the salt efflorescence. The treatment gives a pearly effect and it is permeable to water vapor and it also blocks the salt efflorescence.

SPECIFICATIONS

Composition: solution of poly-methyl-siloxane in hydrocarbon solvents.

Appearance of the treated surface: natural, unchanged from the initial state.

Permeability to water vapor: excellent.

Water resistance: excellent.

Solvents: aliphatic and aromatic hydrocarbons.

Active substance: 6-7%.

Application: brush, roller.

Dilution: ready to use.

Yield: 3-5 sqm/lit, 1 coat.

Drying time: quickly, but acquires its final effect only after a week or so at a temperature above +5 ° C.

METHOD OF USE

Cracks must be adequately widened and filled with stucco or similar products. If old paint is present, remove any peeling parts that are not completely adhered by wetting the surface and scraping or using a high-pressure water jet machine. Remove any dust, smog or other deposits by brushing. Before applying any product, make sure that the surface is thoroughly dried and aged (4-5 weeks).

Apply **Dry Sil** up to saturation of absorption of the surface; in case of rain wait 3 days before the treatment.

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

Protect from frost.

Packaging: 1 – 5 – 25 lt.

Color: transparent.

Washing tools: use white spirit immediately after use.

Specification Item

> Protect all surfaces not subject to application of paint.

> Preparation of the substrate by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt.

> Application of one coat up to saturation of absorption of solvent-based **Dry Sil** (Caf) ready to use with brush or roller, respecting a consumption of about 0,200-0,300 lt/sqm.

> All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.