



ECO WASH MURALE SATINATO – *water based wall enamels*

Water-based enamel specific for wall, odorless, non-toxic, non-flammable, washable and with high coverage. It is formulated with special acrylic dispersions in water, with excellent resistance to light and weathering. Effectively protects the walls from the aggressive of dirt and usury, allowing you to keep surfaces looking like new. For its safety and absence of smell it is particularly suitable for indoors and hospital and where you want to restore in a short time the habitability of the premises.

SPECIFICATIONS

Composition: top quality acrylic resins.

Nature of the pigments: inorganic and organic highly resistant to weathering.

Solid content: 53%±2.

Recommended film thickness per coat: 40-60 µ.

Dried product appearance: satin.

Viscosity at 20 ° C: 15000 cps + - 1500 (A6 20 ')

Application: brush, roller, spray.

Dilution: 10% approx.. with water.

Yield: 6-7 sqm/lt, according to the substrate.

Drying time: 3 to 4 hours in normal conditions of temperature and humidity.

Recoat: 12-18 hours under normal conditions of temperature and humidity.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *New surfaces:* be sure that the plaster is completely seasoned (at least 4-5 weeks). Apply a coat of **Hydrocril**. When dry, apply two layers of **Eco Wash Murale Satinato**, waiting 5-6 hours between coats.

- *Already painted surface:* remove any scraps; eliminate the cracks with stucco, if necessary; then proceed as above.

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5°C and +35°C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

Packaging: 4 – 14 L.

Color: white, Allegro color chart, NCS color chart, tints on request.

The coloring is possible with the Tinting System **Allegro**.

Washing tools: use water immediately after use.

Specification Item

> Protect all surfaces not subject to application of paint.

> Preparation of the surface by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt. If the surfaces to be treated were covered with organic paints is advisable the total removal of these paintings.

> Application of water-based enamel for large surface **Eco Wash Murale Satinato** (Caf), washable and with high covering power by roller, brush or spray in two layers, equivalent to a total consumption of 0,2 lt/sqm, after preparing the substrate with a coat of acrylic water-based primer **Hydrocril**.

> All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.