



ECO WASH SATINATO – *water based enamels*

Water-based enamel eco-friendly, odorless, non-toxic, non-flammable with an elegant satin finish. It is formulated with special acrylic dispersions in water, free of charge, it is easy to apply and universal. It has excellent resistance to light and weathering. It can be used on various substrates both inside and outside, such as wood, doors, fixtures, furniture and other wood products, plaster, cement, etc.. For its safety and the absence of smell it is particularly suitable for indoors and hospital and where you want to restore in a short time the habitability of the premises.

SPECIFICATIONS

Composition: top quality acrylic resins.

Nature of the pigments: inorganic and organic highly resistant to weathering, amorphous silica, calcium carbonate.

Solid content: 49%±2.

Recommended film thickness per coat: 25-35 µ.

Dried product appearance: satin.

Gloss of the film: 60 ° = 30

Viscosity at 20 ° C: 20-25"

Application: brush, roller, spray.

Dilution: 10% approx. with water.

Yield: 6-7 sqm/lit, according to the substrate.

Drying time: to touch 1 hour, hardened in depth 10-12 hours.

Recoat: 18-24 hours under normal conditions of temperature and humidity.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *New surfaces:* Apply a coat of **Eco Wash Primer**. When dry, apply two layers of **Eco Wash Satinato** (Caf), waiting 18-24 hours between coats.

- *Already painted surface:* remove any scraps; eliminate the cracks with stucco, if necessary; then proceed as above.

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5°C and +35°C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.



USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

Packaging: 0,750 – 2,5 – 16 L.

Color: white, Allegro color chart, NCS color chart, tints on request.

The coloring is possible with the Tinting System 

Washing tools: use water immediately after use.

Specification Item

> Protect all surfaces not subject to application of paint.

> Preparation of the substrate by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt. If the surfaces to be treated were covered with organic paints is advisable the total removal of these paintings.

> Application of two coats of water-based enamel with satin finishing **Eco Wash Satinato** (Caf), washable and with high covering power by roller, brush or spray, after preparing the substrate with a coat of acrylic water-based primer **Eco Wash Primer** (Caf).

> All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.