



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

EXPRESS – paint remover

Wall paint stripper WITHOUT METHYLENE CHLORIDE, conforms to the European Parliament and Council Decision 455/2009 / EC. Specific for wall paints, plastic coatings, fillers and all the wall paintings based on synthetic resins. It has a density such as to allow a perfect application both on horizontal and vertical surfaces.

SPECIFICATIONS

Composition: dichloromethane, hydrocarbon solvents, paraffin, surfactants.

Appearance of product: gelatinous, transparent.

Application: brush, spatula.

Dilution: ready to use.

Grip time: variable according to the nature of the paint and the thickness; generally from a few minutes for the conventional paints up to a few hours for those catalyzed.

Time before the partial drying: the product remains moist and active, depending on the amount applied, for several hours after the application; where it becomes necessary repeat the application of a new layer.

Action time: 10-30 minutes, depending on the thickness of the paint.

Yield: 2 sqm/L, 1 coat. (depending on the application, the type and thickness of the paint, the surface features to be treated and the ambient temperature).

METHOD OF USE

Mix the product after opening. Apply **Express** (Caf) distributing the product uniformly over the surface to be treated, with a brush or a spatula, in a thickness of about 2-3 mm. Wait until the paint is completely shriveled and raised; remove all with a spatula. any residue can be removed with a further application.

Warnings: Do not shake before use. Open the cap carefully because the product may discharge violently, if under pressure. Subsequently cover with a cloth the mouth and slowly pull the ring, up to cause the deflation. Keep the container away from the face. Use protective goggles and gloves during application, keep the container well closed, away from heat sources and in a cool and dry environment. Do not apply on warm surfaces or exposed by the sun. The wastes generated from the use of paint stripper must always be considered as dangerous and disposed of by specialist companies. It assumes no responsibility for damages resulting from a different container handling.

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application in presence of strong wind,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

Packaging: 0,750 – 4 – 20 L.

Color: transparent.

Washing tools: use white spirit immediately after use.

NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

Specification Item

- > Protect all surfaces not subject to application of paint.
- > Preparation of the substrate by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt.
- > Application of one coat of absorption of wall paint stripper **Express** (Caf) distributing the product uniformly over the surface to be treated by brush or spatula, in the thickness of 2-3 mm; wait until the paint is completely shriveled and raised and then remove all with a spatula.
- > All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5°C and +35°C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.