



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

MICOSTOP SOLUZIONE – *anti-mold/anti-condensation*

Sanitizing solution for walls with high penetration power. For the prevention and rehabilitation of the areas attacked by mold. Prepare the walls to the painting with specific products for the restoration.

SPECIFICATIONS

Composition: aqueous solution of restorative compounds with broad-spectrum of action.

Active substance: about 2%.

Dilution: ready to use.

Application: brush.

Yield: 10-12 sqm/liter with an application according to the degree of absorption.

METHOD OF USE

Apply the product directly on walls previously treated with **Micostop Spray** (Caf). Let it dry and proceed with the application of anti-mould paints Micosop/Hydromur Plus/Isotherm.

For best result, we recommend the application of the complete **Antimould Cycle: Micostop Spray + Micostop Soluzione + Micosop/Hydromur Plus/Isotherm.**

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

USEFUL TIPS:

- Store at room temperature.
- Keep out of reach of children.
- In case of contact with skin, wash immediately with water.
- Make sure the room is well ventilated during application.
- Do not spray on plants or tissues.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

Packaging: 1 – 5 L.

Color: transparent.

Washing tools: use water immediately after use.

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

Specification Item

- > Protect all surfaces not subject to application of paint.
- > Preparation of the substrate by applying **Micostop Spray** (CAF) until the complete elimination of any existing mold and subsequent washing.
- > Application sanitizing solution **Micostop Soluzione** (CAF) on walls previously treated with **Micostop Spray** (Caf)
- > All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.