



MURINEX 030 – washable paints

Top quality washable paint for outdoor and indoor use. Formulated with special resins and selected pigments that give the product a high covering power and an excellent resistance to abrasion ensuring a long life. The colors are stable to light, not flaming, leaving no signs of recovery. His final look is smooth and satisfies the most refined taste. It can be applied on various surfaces such as concrete, gypsum, plaster, fiber cement, wood, plasterboard, properly treated.

SPECIFICATIONS

Composition: copolymers vinylversatic based, titanium dioxide and selected fillers.

Nature of the pigments: titanium dioxide, kaolin, silicates, crystalline calcium carbonate.

Dried product appearance: mat.

Solid content: 60%±1.

Particle size: 3-5 µ.

Viscosity at 20 ° C: 20.000 cps ± 1.500 cps (A6 20').

Average thickness of the film: 50 µ.

Rubbing resistance: excellent

Strength of adhesion to the substrate: good

Ph: 8-8.5

Application: brush, roller, spray.

Dilution: 30-40% approx.. with water.

Yield: 6-7 sqm/lt, for 2 coats.

Drying time: to touch 1 hour, hardened in depth 10-12 hours.

Recoat: 5-6 hours, dry in depth approx 18 hours, under normal conditions of temperature and humidity.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *New surfaces:* Apply a coat water-based fixative **Hydrocril**, diluted 300% with water. Once dried, apply two coats of **Murinex 030**, waiting for the complete drying between one layer and another.

- *Already painted surface:* remove not properly anchored parts, scraping and brushing; eliminate the cracks with stucco, if necessary; then proceed as above.

USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).



CLIMATIC CONDITIONS

NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. - 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 - fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

Protect from frost.

Packaging: 0,750 - 2,5 - 4 - 14 L.

Color: white, Allegro color chart, NCS color chart, tints on request.

The coloring is possible with the Tinting System **Allegro**.

Washing tools: use water immediately after use.

Specification Item

> Protect all surfaces not subject to application of paint.

> Preparation of the substrate by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt. If the surfaces to be treated were covered with organic paints is advisable the total removal of these paintings.

> Application of two coats of top quality washable paint for outdoor and indoor use **Murinex 030** (Caf), by roller, brush or spray, equivalent to a total consumption of 0.200 l/sqm, after preparing the undercoat with a coat of water-based primer **Hydrocristil** (Caf).

> All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.