



PITTURA PER IMPIANTI SPORTIVI – *special products*

Acrylic water-based paint for sports facilities in bituminous conglomerate with remarkable properties of adhesion to the substrate and excellent elasticity. The use of pigments extremely resistant to exterior provides excellent color stability. Thanks to its extreme ease of use, it does not require for its application the use of special equipment. Extremely resistant to weathering, it retains its characteristics over time.

SPECIFICATIONS

Composition: acrylic resins, styrene-acrylic resins, selected silica, and minerals of high wear resistance

Dried product appearance: matt.

Particle size: 60-70 μ .

Average film thickness: 100 -150 μ .

Viscosity at 20°C: 520,000 cps $\pm$ 2,000 cps (A6 20 ').

Abrasion resistance: excellent.

Weathering resistance: excellent.

Strength of adhesion to the substrate: excellent.

Ph: 8,5-9.

Application: brush, roller.

Dilution: 20-25% water.

Yield: 10 sqm./lt, one coat.

Drying time: dried in depth after 18 hours depending on the environmental conditions.

METHOD OF USE

Before the application of the product proceed to the surface cleaning, to remove all traces of dirt, dust, etc. which would reduce the adhesion of the product to the support. Wait until the surface is clean and completely dry. Start applying the first coat of paint diluted 25% with water. Leave at least 12 hours, then apply two coats of diluted product at 15-20% with water, waiting 24 hours between. Wait at least 48 hours after the last coat of paint before using the surface.

USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5°C and +35°C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of strong wind,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

Protect from frost.

Packaging: 14 L.

Color: white, grey, oxide green, oxide red.

Washing tools: use water immediately after use.

Specification Item

> Protect all surfaces not subject to application of paint.

> Preparation of the surface by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt.

> Application of several coats of acrylic water-based paint for sports facilities in bituminous conglomerate **Pittura per Impianti Sportivi** (CAF) which the first diluted at 25% with water and the others at 15%, spaced from each other by 18-24 hours.

> All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5 °C and +35 °C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.