



RAPITERM SATINATO – industrial products

Synthetic enamel with satin finished, fast drying at room temperature. Very resistant on the outside because it is made from the finest synthetic resins, which are exempt from physical film forming, and selected pigments of great strength to light and weathering. For its special characteristics of anchorage and elasticity, it is used in the finishing of metal artifacts such as industrial vehicles, agricultural machinery, construction, tools, heaters, etc ...

SPECIFICATIONS

Composition: short oil alkyd resin, non-yellowing.

Nature of the pigments: inorganic and organic highly resistant to weathering.

Solid content: 62%±2.

Recommended film thickness per coat: 25-35 µ.

Dried product appearance: satin.

Viscosity at 20 ° C: 20-22".

Application: brush, spray.

Dilution: 5% approx. with nitro thinner, 20-25% if used by spray.

Yield: 5 sqm/lt, 1 coat.

Drying time: 30 minutes, hardened in depth 18-20 hours.

Recoat: 18-24 hours under normal conditions of temperature and humidity.

METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *Never painted surfaces:* brush and sand the surface, removing all traces of rust; clean and degrease with nitro thinner. Treat the surface with a coat of **Antiruggine R.E.** (Caf); wait 16-24 hours and apply two coats of **Rapiterm Satinato**(Caf).

- *Already painted surfaces:* remove the parts of paint not well anchored with the paint stripper **Express** (Caf); In case of application on old paint, it is advisable to make sure of their resistance and compatibility with the new painting cycle; then proceed as above.

CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5 °C and +35 °C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.



USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

Protect from frost.

Packaging: 0,750 – 4 – 16 lt.

Color: white, black, RAL colors.

Washing tools: use nitro thinner immediately after use.

NUOVA CAF S.r.l.

Via L. Einaudi, 6/7_Z.I. – 61032 Fano (PU)_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

www.nuovacaf.it - info@nuovacaf.it

Specification Item

- > Protect all surfaces not subject to application of paint.
- > Preparation of the substrate by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt.
- > Application of one coat of solvent-based anticorrosive undercoat **Antiruggine R.E.** (Caf) by brush or spray. Once dried, application of two coats of synthetic solvent-based top quality enamel with satin finishing and fast drying **Rapiterm Satinato** (Caf), waiting 18-24 hours between coats, making a dry thickness of 25-35 µ per coat.
- > All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5°C and +35°C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.