



## FOND GRIP – *acrylic outdoor wall coating*

Fond Grip is an acrylic undercoat connecting painting for exterior use with high filling power. Particularly suitable in those cases in which you make restores and do not want to see the difference in particle size between the new plaster restored and the old one.

### SPECIFICATIONS

**Composition:** styrene-acrylic resins.

**Application:** brush, roller.

**Dilution:** 20-30% with water.

**Yield:** 4-5 sq.m./L, with two layers according to the substrate.

**Drying time:** dried in depth after 24 hours depending on the environmental conditions.

### METHOD OF USE

Ensure that the surface is thoroughly dried and aged. If necessary, take measures to reconstruct or consolidate the surface by using specific products. Remove any mold, efflorescence and any old peeling paint by brushing or washing. Remove any deposits of dust, smog or other by brushing. Level any irregularities in the surface and treat holes, cracks, crevices and gaps.

- *New surfaces:* be sure that the plaster is completely seasoned (at least 4-5 weeks). Apply a coat of **Primer Consolidante** (Caf). Allow to dry, then complete applying **Fond Grip** (Caf) by brush or roller, spreading the product uniformly; once dry (18-24 hours) apply the second layer.

- *Already painted surface:* remove the old paint with paint remover **Express** (Caf) and remove any scraps; eliminate the cracks with stucco, if necessary; then proceed applying a layer of nitro-based primer **Fix Nitro alla Pliolite** (Caf). Then proceed applying **Fond Grip** (Caf) by brush or roller, spreading the product uniformly; once dry (18-24 hours) apply the second layer.

### CLIMATIC CONDITIONS

To avoid compromising the optimal performance of the product, we recommend the application in specific climatic conditions:

- Apply at temperatures between +5°C and +35°C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in presence of moisture;
- The painted surface must be kept away from rain and humidity for 48 hours.

### USEFUL TIPS:

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

The technical information contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.



**NUOVA CAF S.r.l.**

Via L. Einaudi, 6/7\_Z.I. – 61032 Fano (PU)\_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

[www.nuovacaf.it](http://www.nuovacaf.it) - [info@nuovacaf.it](mailto:info@nuovacaf.it)

Protect from frost.

Packaging: 4 – 14 L.

Color: white.

Washing tools: use water immediately after use.

## Specification Item

> Protect all surfaces not subject to application of paint.

> Preparation of the surface by manual brushing or washing with high pressure washer machine, depending on the nature and intensity of the dirt. If the surfaces to be treated were covered with organic paints is advisable the total removal of these paintings.

> Application by roller or brush of a first coat **Fond Grip** (CAF) followed after 18-24 hours from the application of a second coat of the same product, subject to a consumption refers to two coats of 0,250 L/sq.m, according to the type of support, after preparing the substrate with a consolidating primer **Primer Consolidante** (CAF).

> All applications must be performed on completely dry surfaces, with the ambient temperature and that of the surfaces to be painted between +5°C and +35°C with relative humidity not exceeding 80%. If you ever experience environmental conditions other than those mentioned above, as well as in the presence of wind, dust, smoke, etc ..., the application should not be initiated.