



**NUOVA CAF S.r.l.**

Via L. Einaudi, 6/7\_Z.I. – 61032 Fano (PU)\_ Italy

Tel. +39 0721 854235 – fax +39 0721 854596

[www.nuovacaf.it](http://www.nuovacaf.it) - [info@nuovacaf.it](mailto:info@nuovacaf.it)

## VELANTE PER CALCE – *lime products*

Top quality water-based paint for exterior walls with good coverage features and performance, suitable for the surface protection of lime cycles. The quality of the raw materials used in the formulation ensures the product qualities of remarkable durability and protection of surfaces, even in conditions of considerable environmental aggression.

### SPECIFICATIONS

**Composition:** synthetic resins, titanium dioxide, ventilated quartz and selected aggregates

**Appearance of dried product:** matt.

**Solid content:** 74%± 2.

**Particle size:** 60-70 µ

**Viscosity at 20 °C:** 22,000 cps ± 1,500 cps (A6 20 ')

**Abrasion resistance:** excellent.

**Average coating thickness:** 60-70 µ.

**Weathering resistance:** excellent.

**Strength of adhesion to the substrate:** excellent.

**Application:** brush, roller.

**Dilution:** 20-30% water.

**Yield:** 7-8 sq.m./L, depending on the surface.

**Drying time:** 24 hours, depending on the environmental conditions.

### METHOD OF USE

Apply on surfaces treated with lime-based products if you want to increase the protective level or uniform color variations. Wait until the substrate is well dried, then proceed with the application of a coat of **Velante per Calce** (Caf), taking care to spread the product well to not create accumulations of material.

### CLIMATE CONDITIONS

To avoid compromising the optimal appearance and performance of the product we recommended that it be applied only in specific climate conditions:

- Apply to temperatures between + 5 ° C and + 35 ° C;
- Avoid the application on surfaces heated by strong sunlight,
- Avoid application when rain is imminent,
- Avoid application in case of humidity;
- Surface must be protected from rain and damp for approximately 48 hours.

### USEFUL TIPS

- Store at room temperature.
- Close the container tightly after each use.
- Protect surfaces not to be painted (windows, tiles, glass etc ...).

**Protect from frost.**

**Packaging:** 14 L.

**Color:** white, Allegro color chart.

**Washing tools:** use water immediately after use.

The technical informations contained in this technical sheet are based on our practical experience and laboratory testing and are purely indicative. We offer products and operating systems in perfect correspondence with the highest quality standards, provided that the instructions for use are followed in accordance with the needs and the professional knowledge of utilization. The application of the products takes place outside of our control and therefore is under the sole responsibility of the customer. Our technical department is always at your complete disposal to provide any further information or clarification.